Product Information Sheet # PB01/PB02



SUMMARY

shipped at RT; store at RT

For research use only

- available in high pharmaceutical quality
- free of carbohydrates
- high solubility in aqueous solution up to 50% [w/v]
- stays soluble at 4 °C in aqueous solution
- usable pH-range 5 8.5
- average molecular weight of 3 kD

Applications

- western blot / dot blot
- ELISA
- surface coating
- gene-chip technology (replacement of acetylated BSA)

Advantages

- better blocking capacity than BSA
- virtually no background in western blotting
- increase of signal-to-noise ratio in ELISA
- solubility guaranteed up to 50% [w/v]
- low price

Perfect-Block was developed to improve the sensitivity of your standard protein detection systems and to increase signal-to-noise ratio values in various research applications like Western blot, ELISA, gene-chip technology or coating of surfaces.

Perfect-Block consists of highly purified gelatine proteins in superior and pharmaceutical research quality. Perfect-Block can be used as blocking reagent in your standard detection systems without changing your protocol.

Perfect-Block has been tested in several applications using different protein samples and various protocols. A standard Western blot protocol is provided below.

References

Fritsche, J., Reber, B.F.-X., Schindelholz, B., Bandtlow, C.E.; Mol. Cell. Neuroscience (MCN), Vol. 14(4), p. 398-418; 1999 used in Chen, M.S., Huber, A.B., van der Haar, M.E., Frank, M., Schnell, L., Spillmann, A.A., Christ, F. and Schwab, M.E.; Nature, Vol. 403, p.434-438; 2000

MoBiTec GmbH, Germany Phone: +49 551 70722 0 Fax: +49 551 70722 22 E-Mail: info@mobitec.com www.mobitec.com

Revised June 2013

Perfect-BlockTM

Product Information Sheet

PB01/PB02



Productdata

Catalognumber:PB01PB02Quantity:100 g500 g

Description: Highly purified gelatine proteins in pharmaceutical quality in

accordance with DAC 1986, 1st supplement 1989

Recommendation for declaration: Gelatine protein

Appearance: Light coloured powder

Odour: Very low odour level

Solubility: Excellently soluble in cold and warm water

Chemical and Physical Data:Test MethodProtein content of dry substancesappr. 97%Kjeldahl (Nx5.55)Dry substances (105 °C, 16 h)91.5 – 96.0%Eur. Ph., 1986Ash (550 °C)60 °CEur. Ph. 1986

Ash (550 °C) < 0.9% Eur. Ph., 1986 pH (20%, room temperature) 5.0-6.4 Potentiometer

Viscosity (20%, 25°C) 3.2 – 4.7 mPa s

Heavy metals < 40 ppm Eur. Ph., 1986

Bulk density 250 – 400 g/l

Average molecular weight appr. 3,000 D GPC with collagen weight markers

Microbiological Data

Aerobic bacterial count < 500/g Eur. Ph., 1986
Enterobacteriaceae nil/g Eur. Ph., 1986
Escherichia coli nil/g Eur. Ph., 1986
Clostridia nil/g AFNOR NF V 59-106

Shelf Life:

Under dry and odourless conditions PB01 can be stored for at least 2 years after delivery date without loss of quality.

This information is based on our present state of knowledge and is intended to provide general information on our products and their uses. It should not therefore be construed as guaranteeing specific properties of the products described or their suitability for a particular application.

Any existing industrial property rights must be observed. The quality of our products is guaranteed under our General Conditions of Sale, and the quality assurance system of the manufacturer in accordance with DIN ISO 9001 (EN 29001).

MobiTec GmbH, Germany Phone: +49 551 70722 0 Fax: +49 551 70722 22 E-Mail: info@mobitec.com www.mobitec.com

Revised June 2013

Product Information Sheet # PB01/PB02



Order Information, Shipping and Storage

| Order# | Product | Quantity |
|----------------------------|-----------------|----------|
| PB01 | Perfect-BlockTM | 100 g |
| PB02 | Perfect-BlockTM | 500 g |
| shipped at RT; store at RT | | |

Contact and Support

MoBiTec GmbH ● Lotzestrasse 22a ● D-37083 Goettingen ● Germany

Customer Service – General inquiries & orders

phone: +49 (0)551 707 22 0 fax: +49 (0)551 707 22 22 e-mail: order@mobitec.com **Technical Service - Product information**

phone: +49 (0)551 707 22 70 fax: +49 (0)551 707 22 77 e-mail: info@mobitec.com

MoBiTec in your area: Find your local distributor at www.mobitec.com

MoBiTec GmbH, Germany Phone: +49 551 70722 0 Fax: +49 551 70722 22 E-Mail: info@mobitec.com www.mobitec.com

Revised June 2013